



VALVOLINE™ ZEREX™ G48® ANTIFREEZE COOLANT

Valvoline ZEREX G48 Antifreeze Coolant is an ethylene glycol-based formulation suitable for passenger cars, light trucks, and heavy-duty vehicles. The formulation is designed for both gasoline and diesel engines. Its low-silicate, low pH, phosphate free European technology protects all cooling system metals, including aluminum, from corrosion. The ASTM and other test data shown on this sheet reflect the high-performance corrosion inhibitor package.

When diluted 50% with water, ZEREX G48 protects modern engine components from winter freezing and summer boil over. The chart at the below provides mixing information. A 50% to 70% concentration range is suggested for optimum corrosion protection. ZEREX G48 is compatible with many brands of coolant commonly available. It contains a high quality defoamer system and will not harm hoses, plastics, or original vehicle finishes.

Call 1-800- TEAM-VAL with questions.

Valvoline ZEREX G48 Antifreeze Coolant is an approved formula for the following specifications:

Audi TL-774-C	MTU MTL 5048
BMW GS 94000	Opel/Vauxhall (until 2000) B040 0240
(Certain Ford & Chrysler)	Porsche (until 1995)
Detroit Diesel 7SE298	Rolls-Royce (from 1998)
DEUTZ DQC CA-14 Approved	Saab 690 1599
DTFR 29C100	Seat TL-774-C
Federal Specification A-A-870A	Škoda TL-774-C
Jaguar	Smart
Jenbacher TA-Nr. 1000-0201	TMC of ATA RP-302B
Liebherr Minimum LH-00-COL3A	Van Hool
MAN Diesel & Turbo Liste 3.3.7	Volvo 2015 (cars) and older
MAN 324 NF	Volvo Truck
Maybach	VW TL-774-C
Mini	Zastava

Valvoline ZEREX G48 Antifreeze Coolant is formulated to meet or exceed the following antifreeze specifications:

ASTM D3306	SAE J1034
ASTM D4985	SAE J814
GM 1899M	SAE J1941
GM 1825M	Tesla

Valvoline recommends that spent coolant never be disposed of by dumping into a septic system, storm sewer or onto the ground. Instead, contact your state or local municipality for instructions on where to and how to properly dispose of this coolant and protect our environment.

If any coolant is spilled onto the ground, contain the spill and call the state authorities and ask for proper instruction on how to clean up the spill.

TRUSTED FOR 150 YEARS™

™Trademark of Valvoline or its subsidiaries, registered in various countries ©2021 Valvoline

ZEREX G48 Antifreeze/Coolant Boil/Freeze Protection	
% Antifreeze	Freezing Point SE/FC
	Boiling Point** SE/FC