

%CO	AFR	%CO	AFR	%CO	AFR
0.1	14.72	3.5	13.20	6.9	11.93
0.2	14.54	3.6	13.15	7.0	11.89
0.3	14.42	3.7	13.12	7.1	11.86
0.4	14.34	3.8	13.08	7.2	11.82
0.5	14.28	3.9	13.03	7.3	11.79
0.6	14.23	4.0	13.00	7.4	11.76
0.7	14.21	4.1	12.96	7.5	11.72
0.8	14.17	4.2	12.93	7.6	11.69
0.9	14.15	4.3	12.90	7.7	11.65
1.0	14.11	4.4	12.86	7.8	11.61
1.1	14.09	4.5	12.83	7.9	11.58
1.2	14.04	4.6	12.80	8.0	11.54
1.3	14.01	4.7	12.75	8.1	11.50
1.4	13.98	4.8	12.70	8.2	11.46
1.5	13.94	4.9	12.66	8.3	11.43
1.6	13.89	5.0	12.64	8.4	11.40
1.7	13.86	5.1	12.59	8.5	11.36
1.8	13.82	5.2	12.54	8.6	11.32
1.9	13.80	5.3	12.51	8.7	11.28
2.0	13.77	5.4	12.46	8.8	11.25
2.1	13.73	5.5	12.43	8.9	11.21
2.2	13.69	5.6	12.40	9.0	11.16
2.3	13.63	5.7	12.37	9.1	11.12
2.4	13.59	5.8	12.30	9.2	11.08
2.5	13.56	5.9	12.25	9.3	11.05
2.6	13.54	6.0	12.25	9.4	11.01
2.7	13.49	6.1	12.22	9.5	10.97
2.8	13.45	6.2	12.18	9.6	10.94
2.9	13.41	6.3	12.13	9.7	10.90
3.0	13.38	6.4	12.10	9.8	10.86
3.1	13.34	6.5	12.09	9.9	10.82
3.2	13.31	6.6	12.03	10.0	10.79
3.3	13.27	6.7	12.00		
3.4	13.24	6.8	11.96		

Idle 750-800 Co 3,5-4,5 = AFR 12,8 -13,2

Lower partial 1500 Co 1,5-3,0 = AFR 13,4 -13,95

3000+ Co 0,2-1,5 = AFR 13,95 -14,5

Full load 3000+ Co 2,0-4,0 = AFR 12,85 -13,2

